



ASIA MACHINES



RADIAL DRILLING MACHINE



MODEL: SER-25

TECHNICAL SPECIFICATIONS

MODEL	SER-25
Drilling Capacity (C.I.)	25mm
Size of Morse Taper	M-T-3
Spindle Stroke	200mm
No. of Spindle Speed	8
Range of spindle Speed	80-1800RPM
Spindle Drive Motor	1HP 1440 RPM
Arm Elevating Motor	0.5HP 1440 RPM
Spindle Drive V-Belt	B-45
Arm Elevating V -Belt	A-19
Working Table (L x W x H)	300 x 250 x 250mm
Drilling Radius Max. / Min.	720 / 365mm
Maximum Drill Head Travel	355mm
Distance from Column to Spindle Max. / Min.	655 / 300mm
Distance from base to spindle Max. /Min.	880 / 175mm
Diameter of column.	130mm
Swivel of arm L/R Side	90°
Base Plate (L x W x H)	1005 x 605 x 125mm
Working Surface	620 x 490mm
No. of Slots / Size	3 / 16mm
Overall Height	1525mm
Wooden Case Size (L x W x H)	1100 x 700 x 1800mm

Standard Equipments: Motor Pulley 2 Nos., Drift Drift

Optional Equipments: Electric Motor & Starter, Coolant Pump & Fittings, V-Belts, Box Table

Note: Above specifications are change without prior notice towards the improvements in our products.